

## FUNCTION

Speed control loop IP.

## VHDL File

spdcontrol.vhd

## Applicable Devices

Spartan 3A DSP, Spartan 6, Kintex 7, Zynq

## Xilinx primitive used

DSP48A/A1/E1

## Sub modules used

dsp4mot.vhd

r32umlite.vhd

## Execution time

Parameters depend

## Introduction

This IP realizes the speed control loop with PI (Proportional Integral) regulator including with anti-windup control. The output is normalized avoid saturation, finally a conversion to rectangular coordinates is applied

## Detailed Description

This module implements the speed loop using PI (Proportional Integral) regulator.

The generic PI formula is the following equation:

$$u_n = K_p e_n + K_i \frac{T}{T_i} \sum_{k=0}^n e_n$$

*Equation 1: generic PI regulator*

detailed

$$e_n = \text{spdset} - \text{spdact}$$

*Equation 2: the error*

$$e_s = \sum_{k=0}^n e_n$$

*Equation 3: error history*

$$u_n = kmpro e_n 2^{-c\_pro\_dln2} + kmint 2^{-c\_int\_dln2} \sum_{k=0}^n e_n$$

*Equation 4: the IP core*

$$u_{ns} = -outlim \leq u_n \leq outlim$$

*Equation 5: Saturation of PI result*

$$\begin{aligned} outvix &= u_{ns} kmultx \\ outvly &= u_{ns} kmulty \end{aligned}$$

*Equation 6: signed modulo to vector rectangular*

Where:

$u_n$  is the output value at the time  $n \cdot T$   
 $e_n$  is the error at the time  $n \cdot T$   
 $e_s$  is the sum of all errors  
 $K_p$  is the proportional gain  
 $K_i$  is the integrative gain  
 $T_i$  is the time constant of the integral  
 $T$  is the sampling period

The calculation begins when the **start** signal is driven high for 1 clock cycle; the process terminates when the module sets the **finish** signal high for 1 clock cycle.

The set-point of the PI is the **spdset[31:0]** SIGNED32 argument and the feedback value is the **spdact[17:0]** SIGNED32 argument. The error is calculated as **spdset - spdact**.

The integrative accumulator is post increment of :  $e_n$   
 The anti-windup is implemented by post increment of :  $-e_n(c\_indwp\_kdiv + 2^{-c\_indwp\_dln2})$

The **kmpro[31:0]** BINARY32 (IEEE 754 32 bits floating point) argument is the multiplier of the proportional part of the PI module; referring to **Error! Reference source not found.** and **Error! Reference source not found.**

$$\frac{kmpro}{2^{c\_pro\_dln2}} = K_p$$

The **kmint[31:0]** BINARY32 (IEEE 754 32 bits floating point) argument is the multiplier of the integrator part of the regulator; referring to **Error! Reference source not found.** and to **Error! Reference source not found.**

$$\frac{kmint}{2^{c\_int\_dln2}} = K_i \left( \frac{T}{T_i} \right)$$

The result of PI is saturated to  $\pm$  **outlim[16:0]** UNSIGNED17.

Finally the **kmultx[17:0]** SIGNED18 is multiplied to produce output **outvalx[17:0]** SIGNED18, **kmulty[17:0]** SIGNED18 is multiplied to produce output **outvaly[17:0]** SIGNED18 and **finish** is asserted for just one clock .

The anti-windup is applied when saturation occur. In case of saturation the integrator is reduced by quantity proportional of last error.

$$e_s = e_s - (c\_indw\_kdiv + 2^{c\_indwp\_dln2})e_r 2^{-c\_indp\_dln2}$$

## PARAMETERS

Parameter	Type	Values	Default	Description
C_FAMILY	string	spartan3adsp spartan6 kintex7	zynq	Xilinx FPGA Family name
C_PRO_DLN2	integer	0..-	1	Base 2 logarithm of proportional error divisor
C_INT_DLN2	integer	0..-	5	Base 2 logarithm of integrative error divisor
C_INDWP_DLN2	integer		1	Base 2 logarithm of integrative maximum error for anti windup
C_INDWP_KDIV	integer		1	Integer maximum error for anti windup

## SIGNALS

Signal	I/O	Description
clock	IN	Clock (rising edge).
reset	IN	Reset. Active high.
start	IN	Start calculation. Active high. The pulse width must be of 1 clock cycle.
spdset[31:0]	IN	Set point (SIGNED32) of the regulator.
spdact[31:0]	IN	Feedback value (SIGNED32) of the regulator.
kmpro[31:0]	IN	Proportional gain of the regulator (BINARY32).
kmint[31:0]	IN	Integral gain of the regulator (BINARY32).
outlim[16:0]	IN	Output limiter (saturation value) (UNSIGNED17).
kmultx[17:0]	IN	Output multiplier for X-coordinate (SIGNED18).
kmulty[17:0]	IN	Output multiplier for Y-coordinate (SIGNED18).
outvix[17:0]	IN	Output value for X-coordinate (SIGNED18).
outvly[17:0]	IN	Output value for Y-coordinate (SIGNED18).
finish	OUT	Output available. Active high. The pulse width is of 1 clock cycle.

### TIMING PERFORMANCE AND RESOURCE USAGE

This section provides data on the timing performance and resource utilization of the core. Performance has been obtained on one representative device from the Spartan-3 Generation and Spartan 6 families of FPGAs. The following tables lists the devices used for characterization.

#### Device Utilization

Device Utilization Summary (estimated values)	
Logic Utilization	ZYNQ
Number of Slice Registers	534
Number of Slice LUTs	1000
Number of fully used LUT-FF pairs	420
Number of DSP48E1s	1

#### Execution time

output	input	clock cycles <sup>1</sup>
finish	start	146

<sup>1</sup> Using default parameters.

## Reference Documents

1. Xilinx LogiCORE IP DSP48 Macro V2.1 [ DS754 March 1, 2011 ]

## Support

QDESYS provides technical support for this LogiCORE product when used as described in the product documentation.

QDESYS cannot guarantee timing, functionality, or support of product if implemented in devices that are not defined in the documentation, if customized beyond that allowed in the product documentation, or if changes are made to any section of the design labeled DO NOT MODIFY.

## Ordering Information

For information on pricing and availability of QDESYS modules and software, please contact [info@qdesys.com](mailto:info@qdesys.com)

## Revision History

Date	Version	Description
November 23, 2017	1.0	Initial QDeSys release
November 6, 2019	1.2	Correct interface table

## Disclaimer

In disclosing the information contained in this document QDeSys assumes no obligation to correct any errors herein contained, or to advise you of any corrections or updates. QDeSys expressly disclaims any liability in connection with technical support or assistance that may be provided to you in connection with the information.

THE DOCUMENTATION IS DISCLOSED TO YOU "AS-IS" WITH NO WARRANTY OF ANY KIND. QDESYS MAKES NO OTHER WARRANTIES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, REGARDING THE DOCUMENTATION, INCLUDING ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT OF THIRD-PARTY RIGHTS. IN NO EVENT WILL QDESYS BE LIABLE FOR ANY CONSEQUENTIAL, INDIRECT, EXEMPLARY, SPECIAL, OR INCIDENTAL DAMAGES, INCLUDING ANY LOSS OF DATA OR LOST PROFITS, ARISING FROM YOUR USE OF THE DOCUMENTATION